

XPSfoamTM

ADVANCED UNDERLAY SYSTEMS

Classic Underlay

Underlay
for **effective**
performance
on wood
subfloors

MADE IN
BRITAIN




The UK's only manufacturer of XPS underlay

mm

Classic Underlay

for Wood & Laminate Floors

The XPS 3mm Classic Underlay is easy to install and comes in a fan-fold format. It offers excellent noise reduction, levelling properties and thermal insulation. It's designed for use with all wood and laminate flooring and is 100% recyclable.



3mm thick for effective performance on wood subfloors

3-Way Insulation

Warmer

keeps cold out & warmth in: 1.2 Tog



Quieter

absorbs noise by up to 19dB



Drier

non-absorbing



Levels & Supports

Smooths

levels minor subfloor imperfections



Supports

& braces board joints



Resilient

withstands high loads <math>< 5T/m^2</math>



Durable

mould resistant



Easy to Install

Lightweight

& easy to cut



20 boards

1.2m x 0.4m each



9.6m²

area coverage



Technical Specification

Description	UoM	3mm Classic
Finish	-	Fan-Fold Board
Dimension	mm	1200x400
Thickness	mm	3
Thickness Tolerance	mm	0.5
Dimensional Tolerance	mm	2.5
Foam Density	kg/m ³	35
Thermal Conductivity	W/(m.K)	0.015
Compression Strength	t/m ²	5
Water Absorption	vol. %	<0.1
Impact Sound Reduction*	dB	19
Fire Protection Classification	Euro-class	E
Board Colour	-	Blue
Pack Size/no. Boards per Pack	-	20 boards
Thermal Resistance	m ² K/w	0.115
Tog Rating	Tog	1.2
Pack Coverage	m ²	9.6

*Sound reduction up to 19dB value

* Technical information valid at the time of publication



Other Products & Thicknesses Available

5mm Classic • 6mm Classic • 3mm Premier • 1.5mm LVT

Tel: 01352 741 683 • Email: office@xpsfoam.co.uk • Web: www.xpsfoam.co.uk